

...THE OPTIMAL WAY OF BOARDING A YACHT.

CARBON FIBRE 0% CORROSION 100% LIGHTWEIGHT PROTECTED SYSTEM BY MULTIPLEX GMBH




...THE MULTIFLAP – 100% CARBON FIBRE LIGHTWEIGHT FOR HEAVYWEIGHT

Extremely light weight yet with maximum load capacity are just two demands made on yachting equipment. As part of multiplex's commitment to pursuing the demand for cutting-edge manufacturing techniques and innovative materials, it has developed the multi-flap – a gangway manufactured from a 100% carbon fibre base. This provides a wide range of benefits exclusive to the use of this special material. The multiflap is light, stable and resistant to deformation. It is also weather-proof, which means that neither wind nor seawater can cause any harm. With a weight of 4.4 kg per metre and a quick, simple fixing system, it can be mounted and dismounted by a single person. The practical hinge system keeps storage space to a minimum.

Multiplex gangways are manufactured with firstclass craftmanship, in line with LR Lloyds Register guidelines.







QUICK INSTALLATION THE MULTIFLAP PROVIDES MAXIMUM FREEDOM OF MOVEMENT AND SAFE ANCHORAGE

FEMALE AND MALE FITTING MADE FROM MIRROR-POLISHED STAINLESS STEEL

WE DEVELOP CUSTOMISED SOLUTIONS



YOUR OWN MULTIFLAP

TOTAL LENGTH: UP TO 9,000 MM TOTAL WIDTH: UP TO 900 MM

FOLDABLE OR NON-FOLDABLE

COLOUR OF YOUR CHOICE

WALKING AREA · TEAK COVERING

· ANTI SLIP SURFACE

HANDRAIL

- · CARBON STANCHIONS WITH ROPE
- · STAINLESS STEEL STANCHIONS WITH ROPE
- · TEAK HANDRAIL WITH CARBON STANCHIONS
- · CARBON HANDRAIL WITH CARBON
- · STANCHIONS


STORAGE BAG COLOUR OF YOUR CHOICE


LED LIGHTING SYSTEM


VESSEL NAME IN FONT, SIZE AND COLOUR OF YOUR CHOICE

LLOYDS CERTIFICATE APPROVED LLOYDS REGISTER LOAD CERTIFICATE

HINGES







A) THE HOISTING SYSTEM SUPPORTS YOU WHEN MOUNTING AND DISMOUNTING THE MULTIFLAP.

B) THE JUMPER SYSTEM ENSURES STABLE POSITIONING OF THE GANGWAY. IT STABILISES THE MULTIFLAP AGAINST THE EFFECT OF WAVES OR OTHER LATERAL MOVEMENTS.

PRODUCTION PERIOD: 8 WEEKS SAFE WORKING LOAD: 250 KG **ESTIMATE WEIGHT:** 4.4 KG PER METRE



DETAILS OF YOUR MULTIFLAP-SYSTEM!



ANTI-SLIP SURFACE



TEAK SURFACE




TEAK HANDRAIL



CARBON HANDRAIL




CARBON STANCHIONS WITH ROPE STAINLESS STEEL STANCHION WITH ROPE



LED ILLUMINATION



BOARDING RAMP



STORAGE BAG



ASK ABOUT OUR OTHER CUSTOMISED SOLUTIONS!

multiplex GmbH Zur Westpier 3 28755 Bremen, Germany

Tel.: +49(0)421 / 61 07 26-0 Fax: +49(0)421 / 61 07 26-80

multiplexgmbh.com

